



# SUPRA



Solutions for all your distribution needs. Supra range performance for refrigerated trucks.



YOU CARRY  
WE CARE

Developed for distribution environments with multiple doors openings, rely on the high performance of the Supra range in your challenging operation.

## SUPERIOR PERFORMANCE

The Supra range achieves superior pulldown and accurate temperature control at all set points. This performance is supported by a large range of evaporators with electric fans providing constant airflow independent of engine speed. Available in multi-temperature throughout the range, Supra offers enhanced load protection for all truck applications.

## HIGH CAPACITY

Extended with three high capacity models, the Supra range is available up to 12 000 Watts. New fans increase airflow by 15% for quick temperature recovery and improved air management. The use of a 7 mm condenser and smaller compressor improve the units efficiency thanks to lower fuel consumption per Watt delivered.

## ROBUST DESIGN

Building on hundreds of thousands of operating hours, Supra demonstrates a robust design both for aesthetics (strong composite material) and components (easy start) to extend the unit lifetime and reduce downtime. Maintenance time is also optimised thanks to easy accessibility.

## INTEGRATING IN YOUR WORKING ENVIRONMENT

Tell us your needs, choose your unit: 5 standard units for volumes from 30 to 90m<sup>3</sup>, multi-temperature available throughout the range, nosemount, undermount, swap bodies units, silent and extreme climates versions\*.

The Supra range offers extreme flexibility to ensure you have the right unit for your operation. The silent version (X Model) drastically reduce the noise levels to blend in your distribution area.

\* For extreme climates versions, please consult the Supra Nordic and Oasis brochures.



		REFRIGERATION CAPACITY (Watts)**				AIRFLOW (m <sup>3</sup> /h)	WEIGHT incl. Evaporator (kg)		
		Road		Standby			S	T	X
		0°C	-20°C	0°C	-20°C				
Mono temperature	Supra 450	4365	2515	3810	2240	1590	340	343	N/A
	Supra 550	5455	3165	4670	2770	2150	391	394	N/A
	Supra 750	6780	3750	5920	3120	2140	429	432	437
	Supra 850	7800	4900	6450	4240	2500	461	464	466
	Supra 1050	9100	5600	7800	5000	3350	617	N/A	621
	Supra 1150	10500	6350	8900	5400	3350	626	N/A	630
	Supra 1250	12000	6900	9100	6300	3350	636	N/A	640
Swap Body	Supra 750 SW	6780	3750	5920	3120	2140	442	N/A	N/A
Under-mount	Supra 850U	7690	4600	6550	3975	2840	453	N/A	N/A
	Supra 950U	10600	6205	7430	5500	2840	553	558	N/A
Multi temperature	Supra 750 MT	6150	3810	5560	3840	Up to 2500	411*	414*	419*
	Supra 850 MT	6350	4500	5050	3750	Up to 2500	443*	446*	448*
	Supra 1150 MT	11150	6450	9150	5600	Up to 3600	576*	N/A	N/A
	Supra 1250 MT	11600	7200	9800	6350	Up to 3600	586*	N/A	N/A
	Supra 1150U MT	10700	5950	10200	5750	Up to 3600	N/A	566*	N/A

## ACCESSORIES

- Battery
- Battery box
- 75 l, 90 l or 200 l fuel tank
- Automatic phase reverser
- Oil filter bypass
- Oil drain extension
- Fuel heater
- Control panel extension cable
- Supply air sensor
- Door switch
- Waterproof box for cab command
- DataCOLD 100, 250 or 500

\* Condenser section only

\*\* Ambient temperature at +30°C (per A.T.P. procedure)